

Dsut Collector Filter Cartridges

TECHNO-LEX



- ü Long filter life and high filtration efficiency on many applications.
- ü Filtration efficiency of 99.99% on 0.5 µm particles.
- ü Enhanced performance due to a unique combination of fiber sizes and a more uniform fiber distribution.
- ü Reduced energy requirements and lower operating costs due to low resistance to airflow.
- ü Flame retardant media available.
- ü Superior to felts, fabrics, cotton cloths, and similar media.

Temperature Resistant : 65°C

Application : Recommended for a wide variety of applications. Good choice for dry, coarse particulate. Economical choice for operations with forced or cyclical filter replacement (independent of pressure drop).

Specification :
Proprietary blend of fine cellulose fibers evenly distributed.
Flame retardant.
Fractional Efficiency 99.99% on 0.5 µm particles.
Construction - Standard galvanized expanded metal liners with 72% open area.
Standard galvanized steel end caps.
Optional stainless steel liners and end caps available.
Top Gasket - Urethane.
Operating Temperature - 150°F / 65°C maximum.

Technomart

Kamrabad, Fullorhat (Near Fullorhat Yuba Sangha), Sonarpur, Kolkata - 700 150, W.B., India
Tel : +91 9830156166 / 9230556166 / 9230518809 Fax : +91 33 2434 6692
e-mail : technomart@vsnl.net, Web : www.techno-filter.com